

# FLUID PENDANT LAMP - EU VERSION

CLAESSON KOIVISTO RUNE ON THE DESIGN "We wanted to give the lamp a form with a certain softness, towards a more natural language and further removed from pure geometry. Fascinated by the way that surface tension governs the curvature of a resting water droplet, we have tried to capture it's essence. The subtle irregularity of Fluid means that their silhouette gently changes depending upon the viewing angle. It also brings a greater light intensity to the lamps'underside - just where you need it."



42 cm 16.5"




23 cm 9''



3,5 cm / l.5"

Ø ll cm / 4.25"



**DESIGNED BY / YEAR OF DESIGN** Claesson Koivisto Rune / 2011 & 2013

### ABOUT THE DESIGNER

Claesson Koivisto Rune is one of Swedens most prominent design studios and the three designers have among many international awards been awarded the annual Swedish design award eight times.

### CATEGORY

Pendant lamp

### ENVIRONMENT

Indoor

### DESCRIPTION

Fluid Pendant Lamp is a modern pendant with personality and ambience. Place the lamp alone over a table, or mix small and large Fluid lamps. Arrange in rows or clusters to create a cosy atmosphere  $\delta$  beautiful light.

### PRODUCTION PROCESS

The Fluid lampshade is made from mouth blown glass, which is frosted silky mat. The edge on top of the lamp is grinded and polished.

### MATERIAL

White silk mat opal glass, lid in Nylon66 with fibre glass.

### **CORD LENGTH** 350 cm /l37.75"

### BULB INCLUDED

Large: No Small: Yes


**CEILING CAP INCLUDED** Yes - White

### DIMMABLE FUNCTION

Large: Yes Small: Yes, if dimmable bulb is used.


### CLEANING AND CARE

Clean with soft dry cloth only. Always switch off the electricity supply before cleaning.



# FLUID PENDANT LAMP - EU VERSION





# This luminaire is compatible with bulb of the energy classes:

### LAMP RATING - SMALL

Voltage Frequency **IP** Rating Classification Socket

220-240VV 50/60Hz IP2O Class II 1 x G9 Max. 40W; Halogen Max. 5W; LED bulb

### LAMP RATING - LARGE

Voltage Frequency **IP** Rating Classification Socket

220-240VV 50/60Hz IP90 Class II I x E27 Max. 60W Max. I3W PL Lamp (self-ballasted) Max. I8W LED bulb

### **BULB SPECIFICATION - SMALL**

Item G9 LED bulb 3W Watt 2301m Lumen Kelvin 2700K 25.000h Lifetime >80 No Dimmable

CRI

### **BULB RECOMMENDATION - SMALL**

| Lamp base          | G9          |
|--------------------|-------------|
| Dimensions         | Ø20 X 60 mm |
| Light source shape | Frosted     |
| Max wattage        | See rating  |
| Light source type  | LED         |

### **BULB RECOMMENDATION - LARGE**

| n |
|---|
|   |
|   |
|   |
|   |

### GENERAL STANDARDS & CERTIFICATES

EU/UK REACH

Directive - EC/I907/2006

Low Voltage Directive (LVD)- 2014/35/EU IEC 60598-I and IEC 6O598-2-I (EU deviations)

ROHS Directive - 2011/65/EU amended RoHS 3 Directive 2015/863

ECO Design Directive - 245/2009/EC

WEEE Directive - 2012/19/EU

CHINA

Fluid Pendant Lamp Small only: CCC GB 7000.201 and GB 7000.1

## **Μυυτο**